

MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY BREATH ALCOHOL PROGRAM

RECEIVED

TNTOX EC/TR IT	MAINTENANCE RI	EPORT	1	By Carol Day at 8:18 am, Apr 10, 20	
INTOX EC/IR II MAINTENANCE REPORT Complete this report at the time of the regular monthly preventive maintenance check (not to exceed 35)					
days). Complete this report whenev	ar the instrument is s	erviced or repai	red and whenever	it is placed	
into service. Retain the original and send a copy within 15 days to the Breath Alcohol Program, DHSS.					
INTOX EC/IR II SN	NAME OF AGENCY		DATE OF INSPECTION	,	
12678	Wentzville Police	Dept.	04/04/2015		
LOCATION OF INSTRUMENT (STREET AND CITY			TIME OF INSPECTION		
1019 Schroeder Creek Blv Wentz			15:45 CDT		
CHECKLIST: Place a mark in the box by each item if found to be satisfactory or is operating within					
established limits. (Write in observed values where determined). Unmarked items must be corrected					
before using instrument.					
X DIAGNOSTIC RECORD					
X BLANK CHECK	£4	X CO2 CHECK			
X FC 1 TEMP	<u> </u>	X FLOW CHECK			
X SRC TEMP		X FCB CHECK			
X DET TEMP	Ī	X CRC COMP CHEC	CK		
X BT TEMP		X CRC CAL CHECK	ζ		
X STD 2 TEMP		X PRINT TEST			
X ETH CHECK		<u> </u>			
BREATH ANALYZER ACCURACY STAND	ADDG				
	HKUD	TOWNDERSED P	THANOL-GAS MIXT	JBE	
SIMULATOR SOLUTION				DATE 01/20/2016	
1 21		OT# AG402002			
SIMULATOR TEMP (34°C ±0.2°C)	SIMULAT	OR S/N	SIMULATOR EXP	DATE	
			1		
X CALIBRATION CHECK - (ONLY ON	E STANDARD IS TO BE	USED PER MAIN	ENANCE REPORT)		
Z CALIBRATION CHECK - (ONLY ON Run three tests using a stan	dard solution. All	three tests mu	st be within ±	% of the standard value	
Pun three tests using a stan	dard solution. All	three tests mu	st be within ±	% of the standard value andard solution being	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED)	dard solution. All 05 or less. Mark tl	three tests mu he box correspo	ist be within ± 9 anding to the st	% of the standard value andard solution being	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X0.10% STANDARD - MUST REAL	dard solution. All 05 or less. Mark to BETWEEN 0.095% AND	three tests muthe box correspondence of the	ast be within ± 5 onding to the st	% of the standard value andard solution being	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ	dard solution. All 05 or less. Mark tl BETWEEN 0.095% AND BETWEEN 0.076% AND	three tests muthe box correspondent of the correspo	ast be within $\pm \frac{1}{2}$ onding to the state $\frac{1}{2}$	% of the standard value candard solution being	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST READ	dard solution. All 05 or less. Mark tl BETWEEN 0.095% AND BETWEEN 0.076% AND	three tests muthe box correspondent of the correspo	ast be within $\pm \frac{1}{2}$ onding to the state $\frac{1}{2}$	of the standard value candard solution being	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST READ 0.04% STANDARD - MUST READ	dard solution. All 05 or less. Mark th BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND	three tests muthe box correspondent of the correspo	ast be within ±5 onding to the state of the	andard solution being	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 25 0.101 g/210L	dard solution. All 05 or less. Mark the BETWEEN 0.095% AND BETWEEN 0.036% AND BETWEEN 0.038% AND	three tests muche box correspondent of the box	st be within ±! onding to the st IVE IVE IVE IVE ITEST 3 157 0.16	ondard solution being	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL	dard solution. All 05 or less. Mark the BETWEEN 0.095% AND BETWEEN 0.036% AND BETWEEN 0.038% AND	three tests muche box correspondent of the box	st be within ±! onding to the st IVE IVE IVE IVE ITEST 3 157 0.16	ondard solution being	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 25 0.101 g/210L	dard solution. All 05 or less. Mark the BETWEEN 0.095% AND BETWEEN 0.036% AND BETWEEN 0.038% AND	three tests muche box correspondent of the box	st be within ±! onding to the st IVE IVE IVE IVE ITEST 3 157 0.16	ondard solution being	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 = 0.101 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 1	dard solution. All 05 or less. Mark to BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 15 0.101 g TESTS IN THE FOLLOW. .0509 2	three tests muche box correspondence of the	test be within ±0 onding to the state to the	Ol g/210L ITENANCE REPORT:	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 -20 0.101 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 1	dard solution. All 05 or less. Mark to BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 15 0.101 g TESTS IN THE FOLLOW. .0509 2	three tests muche box correspondence of the	test be within ±0 onding to the state to the	Ol g/210L ITENANCE REPORT:	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 - 0.101 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 1 LIST ANY NEW FARTS AND DESCRIBE ANY AL SATISFACTORILY AND WITHIN ESTABLISHED	dard solution. All 05 or less. Mark the BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 15 0.101 g TESTS IN THE FOLLOW. .0509 2	three tests muche box correspondence of the	test be within ±0 onding to the state to the	Ol g/210L ITENANCE REPORT:	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 = 0.101 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 1	dard solution. All 05 or less. Mark the BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 15 0.101 g TESTS IN THE FOLLOW. .0509 2	three tests muche box correspondence of the	test be within ±0 onding to the state to the	Ol g/210L ITENANCE REPORT:	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 - 0.101 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 1 LIST ANY NEW FARTS AND DESCRIBE ANY AL SATISFACTORILY AND WITHIN ESTABLISHED	dard solution. All 05 or less. Mark the BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 15 0.101 g TESTS IN THE FOLLOW. .0509 2	three tests muche box correspondence of the	test be within ±0 onding to the state to the	Ol g/210L ITENANCE REPORT:	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 - 0.101 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 1 LIST ANY NEW FARTS AND DESCRIBE ANY AL SATISFACTORILY AND WITHIN ESTABLISHED	dard solution. All 05 or less. Mark the BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 15 0.101 g TESTS IN THE FOLLOW. .0509 2	three tests muche box correspondence of the	test be within ±0 onding to the state to the	Ol g/210L ITENANCE REPORT:	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ TEST 1 - 0.101 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 1 LIST ANY NEW PARTS AND DESCRIBE ANY ALL SATISFACTORILY AND WITHIN ESTABLISHED SATISFACTORILY AND WITHIN ESTABLISHED SATISFACTORILY AND WITHIN ESTABLISHED	dard solution. All 05 or less. Mark the BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 15 0.101 g TESTS IN THE FOLLOW. .0509 2	three tests muche box correspondence of the	test be within ±0 onding to the state to the	Ol g/210L ITENANCE REPORT:	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST REAL 0.08% STANDARD - MUST REAL 0.04% STANDARD - MUST REAL TEST 1 - 0.101 g/210L INDICATE THE NUMBER OF BREATH REFUSALS 0 004 1 LIST ANY NEW FARTS AND DESCRIBE ANY AL SATISFACTORILY AND WITHIN ESTABLISHED	dard solution. All 05 or less. Mark to BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 15 0.101 g TESTS IN THE FOLLOW. .0509 2 TERATION OR MODIFICATION OF	three tests muche box correspondence to the box correspondence of the	st be within ± onding to the state of the st	Ol g/210L ITENANCE REPORT:	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.200 0.04% STANDARD OF BREATH 1.200 0.04% STANDARD DESCRIBE ANY AD 1.200 0.04% STANDARD DESCRIBE ANY AD 1.200 MAINTENANCE 1.2	dard solution. All 05 or less. Mark the BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 15 0.101 g TESTS IN THE FOLLOW. .0509 2 TERATION OR MODIFICATION OR	three tests muche box corresponded to the box correspo	st be within ± onding to the state of the st	Ol g/210L ITENANCE REPORT:	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.00% STANDARD	dard solution. All 05 or less. Mark to BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 15 0.101 g TESTS IN THE FOLLOW. .0509 2 TERATION OR MODIFICATION OF	three tests muche box corresponded to the box correspo	ast be within ±0 onding to the state to the	Ol g/210L ITENANCE REPORT:	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.00% STANDARD	dard solution. All 05 or less. Mark the BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 15 0.101 g TESTS IN THE FOLLOW. .0509 2 TERATION OR MODIFICATION OR	three tests muche box corresponded to the box correspo	ast be within ±0 onding to the state to the	Ol g/210L ITENANCE REPORT:	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.00% STANDARD	dard solution. All 05 or less. Mark the service of less and service of less and the service of less and the service of less and less are service of less are serv	three tests muche box corresponded to the box correspo	ast be within ±0 onding to the state to the	Ol g/210L ITENANCE REPORT:	
Run three tests using a stan and must have a spread of .0 used. (PRINTOUT ATTACHED) X 0.10% STANDARD - MUST READ 0.08% STANDARD - MUST READ 0.04% STANDARD - MUST READ 1.00% STANDARD	dard solution. All 05 or less. Mark the BETWEEN 0.095% AND BETWEEN 0.076% AND BETWEEN 0.038% AND TEST 2 15 0.101 g TESTS IN THE FOLLOW. .0509 2 TERATION OR MODIFICATION OF	three tests muche box correspondence to the box correspondence of the	TEST 3 15 0.10 TEST 3 15 0.10 TEST 3 15 0.10 TEST THE LAST MAIN TEST THE LAST MAIN TEST THE INSTRUMENT	Ol g/210L TTENANCE REPORT: OVER .19 1 T TO OPERATE	



Airgas USA LLC (LAB) 3500 Bernard Street St. Louis, Mo. 63103 Ph: (314) 533-3100 Fax: (314) 533-7328

Certificate of Analysis

<u>Customer Name</u> Intoximeters, Inc. 2081 Cralg Road St. Louis, Mo 63146 Test Date: 21-Jan-2014

Lot # AG402002

Exp. Date 20-Jan-2016 Cyl. Type

Component

Certifled Concentration 0.100 ± 2% BrAC (272 ppm)

Ethanol Nitrogen

Balance

Certification Traceable to N.I.S.T. RGM Ethanol Standards:

Serial No.	Concentration 391.8 ppm 259.8 ppm 209.0 ppm 103.7 ppm	<u>Serial No.</u>	Concentration
EB0010581		EB0010603	392.5 ppm
EB0010570		EB0010559	258.9 ppm
EB0010285		EB0010595	208.9 ppm
EB0010561		EB0010562	104.9 ppm
EB0010681	52,22 ppm	EB0010579	52,94 ppm

Analytical Method:

NDIR

Digitally signed by Quality Control Date: 2014.01.21 13:44:31 -08:00 Reason: Dry gas standard certification of analysis Location: Airgas USA LLC (Lab)

Analyst:

Rod Marsala

ISO 17025:2005 A2LA accredited. Certificate Number 2989.01



STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES BREATH ALCOHOL PROGRAM



TYPE II

MATTHEW J SCHNEIDER

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

DATAMASTER, INTOX EC/IR II, ALCO-SENSOR IV W/PRINTER

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.

DATE 12/31/2013	honse
NUMBER 230344	DIRECTOR OF STATE PUBLIC HEALTH LABORATORY
EXPIRES 12/31/2015	acting director
(O 580-0771 (8-10)	DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES LAS-4 (18-10)



Date Expires 12/31/2016